



SPECIFICATIONS

MODELS	ECONOR (1 auger)								Pull type E80-260INV	NORMAND Pull type (1 auger)			
	E48-200	E54-200	E60-220	E66-220	E72-240	E78-240	E86-260	E94-260		N74-240INV	N92-260INV	N92-280INV	N102-310INV
Recommended horsepower (HP)	16 @ 25	16 @ 25	16 @ 25	25 @ 40	25 @ 40	35 @ 50	40 @ 75	40 @ 75	40 @ 75	25@40	50@75	60@85	85@120
Cutting width	48"	54"	60"	66"	72"	78"	86"	94"	80"	74"	92"	92"	102"
Cutting height	25"	25"	27 1/2"	27 1/2"	27 1/2"	27 1/2"	33 1/2"	33 1/2"	33 1/2"	30"	32"	32"	37 3/4"
Impeller RPM	540	540	540	540	540	540	540	540	540	540	540	540	540
Impeller diameter	20"	20"	22"	22"	24"	24"	26"	26"	26"	24"	26"	28 1/2"	31"
Impeller depth	7"	7"	8"	8"	8 1/2"	8 1/2"	11"	11"	11"	9"	11"	12"	13 1/2"
Number of blades	4	4	4	4	4	4	4	4	4	4	4	4	5
Impeller shaft diameter	1"	1"	1 1/4"	1 1/4"	1 9/16"	1 9/16"	1 9/16"	1 9/16"	1 9/16"	1 9/16"	1 9/16"	1 9/16"	2"
Balanced impeller	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Drum center height	13 1/2"	13 1/2"	14 1/2"	14 1/2"	15 1/2"	15 1/2"	17 1/4"	17 1/4"	17 1/4"	15 1/2"	18 1/2"	19"	20 1/2"
Removable rotary drum	-	-	-	-	-	-	-	-	-	-	-	-	-
Cylinder size	2" X 4"	2" X 4"	2" X 4"	2" X 4"	2" X 4"	2" X 4"	2" X 4"	2" X 4"	2" X 4"	2" X 4"	2 1/2 X 8"	2 1/2 X 8"	2 1/2 X 8"
Length closed	14 1/4"	14 1/4"	14 1/4"	14 1/4"	14 1/4"	14 1/4"	14 1/4"	14 1/4"	14 1/4"	14 1/4"	20 1/4"	20 1/4"	20 1/4"
Chute rotation	Manual	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	-	Opt.	-	-
	Hydraulic cylinder	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	-	Opt.	-	-
	Hydraulic motor(gear)	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Std	Std	Std
Manual deflector	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Hydraulic	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Semi-ind.chute (2nd deflector)	-	-	-	-	-	-	-	-	-	Opt.	Std	Std	Std
Industrial chute	-	-	-	-	-	-	-	-	-	-	Opt.	Opt.	Opt.
24", 48" industrial chute extension	-	-	-	-	-	-	-	-	-	-	Opt.	Opt.	Opt.
Hydraulic telescopic chute	-	-	-	-	-	-	-	-	-	-	Opt.	Opt.	Opt.
Main auger diameter	17"	17"	17"	17"	17"	17"	20"	20"	20"	17"	17"	20"	22"
Upper auger diameter (optional)	-	-	-	-	-	-	-	-	-	-	-	-	-
Balanced auger	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Reversible carbon steel blade	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Hardox 450 blade	-	-	-	-	-	-	-	-	-	Opt.	Opt.	Opt.	Opt.
Stainless blade	-	-	-	-	-	-	-	-	-	Opt.	Opt.	Opt.	Opt.
Tivar blade	-	-	-	-	-	-	-	-	-	Opt.	Opt.	Opt.	Opt.
Lateral blades	-	-	-	-	-	-	-	-	-	Opt.	Opt.	Opt.	Opt.
Adjustable skid shoes carbone steel	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Std	-	Std	Std
Hardox 450 skid shoes	-	-	-	-	-	-	-	-	-	Opt.	Opt.	Opt.	Opt.
Stainless skid shoes	-	-	-	-	-	-	-	-	-	Opt.	Opt.	Opt.	Opt.
Tivar skid shoes	-	-	-	-	-	-	-	-	-	Opt.	Opt.	Opt.	Opt.
Drive chain number	50	50	50	60	60	60	60	60	60	60	80	80	80
Number of safety bolts	2	2	2	2	2	2	2	2	2	2	2	2	3
Bearing-ductile iron casing	-	-	-	-	-	-	-	-	-	Std	Std	Std	Std
(P.T.O. std) shaft	#2	#2	#2	#4	#4	#4	#6	#6	#6	#4	#6	#6	#8
1000/540 RPM reducer	-	-	-	-	-	-	-	-	-	-	-	-	-
Cushion valve	-	-	-	-	-	-	-	-	-	Opt.	Opt.	Opt.	Opt.
Hitch category	1	1	1	1	1	1	2	2	2	Required	Required	Required	Required
Weight(lbs) approx.-1 auger	420	455	506	525	570	640	915	940	980	836	1500	1850	2100

Specifications are subject to change without notice. The weight does not include chute (except Econor) and accessories

Effective June 15, 2010

NORMAND CO. LTD, 340 Taché, Saint-Pascal, Qc Canada G0L 3Y0

(418) 492-2712