

NORMAND®

Co. Ltd

SPECIFICATIONS

MODELS	E48-200	E54-200	E60-220	E66-220	E72-240	E78-240	E86-260	E94-260	E80-260INV	
Recommended horsepower	16 @ 25	16 @ 25	18 @ 40	25 @ 40	25 @ 40	35 @ 50	40 @ 75	40 @ 75	40 @ 75	
Cutting width	48``	54``	60``	66``	72``	78``	86``	94``	80``	
Cutting height	26``	26``	27 ½``	27 ½``	27 ½``	27 ½``	33 ½``	33 ½``	33 ½``	
Fan RPM	540	540	540	540	540	540	540	540	540	
Fan diameter	20``	20``	22``	22``	24``	24``	26``	26``	26``	
Fan shaft diameter	1``	1``	1 ¼``	1 ¼``	1 ¼``	1 9/16``	1 9/16``	1 9/16``	1 9/16``	
Fan width	7``	7``	8``	8``	8 ½``	8 ½``	11``	11``	11``	
Fan height (ground to center)	13 ½``	13 ½``	14 ½``	14 ½``	15 ½``	15 ½``	17 ¼``	17 ¼``	17 ¼``	
Balanced fan	Std	Std	Std	Std	Std	Std	Std	Std	Std	
Auger diameter	17``	17``	17``	17``	17``	17``	20``	20``	20``	
Balanced auger	Std	Std	Std	Std	Std	Std	Std	Std	-	
Chute rotation on polyethylene	Manual	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	-	
	Hydraulic motor	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Std	
	Hydraulic cylinder	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	-	
	Cylinder size	2`` x 4``	2`` x 4``	2`` x 4``	2`` x 4``	2`` x 4``	2`` x 4``	2`` x 4``	2`` x 4``	-
	Cylinder length (total)	14 ¼``	14 ¼``	14 ¼``	14 ¼``	14 ¼``	14 ¼``	14 ¼``	14 ¼``	-
Chute 1 or 2 deflectors	1	1	1	1	1	1	1	1	2	
Manual deflector	Std	Std	Std	Std	Std	Std	Std	Std	Std	
Hydraulic deflector (2`` x 4``)	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	
Reversible carbon steel blade	Std	Std	Std	Std	Std	Std	Std	Std	Std	
Adjustable skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	
Storage foot	Std	Std	Std	Std	Std	Std	Std	Std	Std	
P.T.O. shaft	2	2	2	4	4	4	6	6	6	
P.T.O. chain	50	50	60	60	60	60	60	60	60	
Number of safety bolts	2	2	2	2	2	2	2	2	2	
Hitch category	1	1	1	1	1	1	2	2	2	
Approx. weight (lbs)	420 lbs	455 lbs	506 lbs	525 lbs	570 lbs	690 lbs	925 lbs	952 lbs	980 lbs	