

GENERAL SPECIFICATIONS

MODELS		E48-200	E54-200	E60-200	E66-220	E72-220	E78-240	E86-260	E94-260
Recommended horsepower (hp).		16@25	16@25	16@25	25@40	25@40	35@50	40@75	40@75
Cutting width		48"	54"	60"	66"	72"	78"	86"	94"
Cutting height		26"	26"	26"	27 1/2"	27 1/2"	27 1/2"	33 1/2"	33 1/2"
Fan RPM		540	540	540	540	540	540	540	540
Fan diameter		20"	20"	20"	22"	22"	24"	26"	26"
Fan shaft diameter		1"	1"	1"	1 1/4"	1 1/4"	1 9/16"	1 9/16"	1 9/16"
Fan width		7"	7"	7"	8"	8"	8 1/2"	11"	11"
Fan height (ground to center)		13 1/2"	13 1/2"	13 1/2"	14 1/2"	14 1/2"	15 1/2"	17"	17"
Balanced fan		Std	Std	Std	Std	Std	Std	Std	Std
Auger diameter		17"	17"	17"	17"	17"	17"	20"	20"
Balanced auger		Std	Std	Std	Std	Std	Std	Std	Std
Chute rotation on polyethylene	Manual	Opt.	Opt.	Opt.	Opt	Opt.	Opt.	Opt.	Opt.
	Hydraulic engine	Opt.	Opt.	Opt.	Opt	Opt.	Opt.	Opt.	Opt.
	Hydraulic cylinder	Opt.	Opt.	Opt.	Opt	Opt.	Opt.	Opt.	Opt.
	Cylinder size	2" X 4"	2" X 4"	2" X 4"	2" X 4"	2" X 4"	2" X 4"	2" X 4"	2" X 4"
	Cylinder length (total)	14 1/4"	14 1/4"	14 1/4"	14"	14 1/4"	14 1/4"	14 1/4"	14 1/4"
Manual deflector		Std	Std	Std	Std	Std	Std	Std	Std
Hydraulic deflector (2" x 4")		Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Reversible carbon steel blade		Std	Std	Std	Std	Std	Std	Std	Std
Adjustable skid shoes		Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
P.T.O Shaft		2	2	2	4	4	4	6	6
P.T.O. chain		50	50	50	60	60	60	60	60
Number of safety bolts		2	2	2	2	2	2	2	2
Hitch category		1	1	1	1	1	1	2	2
Approximative weight (lbs)		420	455	470	525	550	690	925	952