



GENERAL SPECIFICATIONS

| MODELS | 1 AUGER | | 1 AUGER | | | | | | 2 AUGERS | | | 1 AUGER | | | | | |
|---------------------------------------|------------------------|---------|---------|-----------|---------|-----------|---------|-----------|----------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| | N54-220 | N60-220 | N68-240 | N68-240TR | N72-240 | N72-240TR | N74-240 | N74-240TR | N82-260L | N54-262 | N60-262 | N74-260 | N74-260TR | N80-260 | N80-260TR | N86-260 | N86-260TR |
| Recommended horse power | 20@25 | 20@25 | 25@40 | 25@40 | 25@40 | 25@40 | 25@40 | 25@40 | 40@65 | 50@75 | 50@75 | 40@75 | 40@75 | 45@75 | 45@75 | 50@75 | 50@75 |
| Cutting width | 54" | 60" | 68" | 68" | 72" | 72" | 74" | 74" | 82" | 54" | 60" | 74" | 74" | 80" | 80" | 86" | 86" |
| Cutting height | 28" | 28" | 30" | 30" | 30" | 30" | 30" | 30" | 32 1/2" | 38" | 38" | 35" | 35" | 35" | 35" | 35" | 35" |
| Impeller RPM | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 |
| Impeller diameter | 22" | 22" | 24" | 24" | 24" | 24" | 24" | 24" | 26" | 26" | 26" | 26" | 26" | 26" | 26" | 26" | 26" |
| Impeller depth | 8" | 8" | 9" | 9" | 9" | 9" | 9" | 9" | 11" | 11" | 11" | 11" | 11" | 11" | 11" | 11" | 11" |
| Number of blades | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 5 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| Impeller shaft diameter | 1 1/4" | 1 1/4" | 1 9/16" | 1 9/16" | 1 9/16" | 1 9/16" | 1 9/16" | 1 9/16" | 1 9/16" | 1 9/16" | 1 9/16" | 1 9/16" | 1 9/16" | 1 9/16" | 1 9/16" | 1 9/16" | 1 9/16" |
| Balanced impeller | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std |
| Drum center height | 15" | 15" | 15 1/2" | 15 1/2" | 15 1/2" | 15 1/2" | 15 1/2" | 15 1/2" | 18 1/2" | 18 1/2" | 18 1/2" | 18 1/2" | 18 1/2" | 18 1/2" | 18 1/2" | 18 1/2" | 18 1/2" |
| Removable rotary drum | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Cylinder size | 2" X 4" | 2" X 4" | 2" X 4" | 2" X 4" | 2" X 4" | 2" X 4" | 2" X 4" | 2" X 4" | 2" X 4" | 2 1/2" X 8" | 2 1/2" X 8" | 2 1/2" X 8" | 2 1/2" X 8" | 2 1/2" X 8" | 2 1/2" X 8" | 2 1/2" X 8" | 2 1/2" X 8" |
| Length closed | 14 1/4" | 14 1/4" | 14 1/4" | 14 1/4" | 14 1/4" | 14 1/4" | 14 1/4" | 14 1/4" | 14 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" |
| Chute rotation | Manual | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | - | - | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| | Hydraulic cylinder | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | - | - | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| | Hydraulic motor (gear) | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| Manual deflector | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std |
| Hydraulic | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| Semi-industrial chute (2nd deflector) | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Std | Std | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| Industrial chute | - | - | - | - | - | - | - | - | - | - | - | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| 24", 48" industrial chute extension | - | - | - | - | - | - | - | - | - | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| Hydraulic telescopic chute | - | - | - | - | - | - | - | - | - | Opt. | Opt. | - | - | - | - | - | - |
| Main auger diameter | 17" | 17" | 17" | 17" | 17" | 17" | 17" | 17" | 19 1/2" | 17" | 17" | 23" | 23" | 23" | 23" | 23" | 23" |
| Upper auger diameter (optional) | - | - | - | - | - | - | - | - | - | 17" | 17" | - | - | - | - | - | - |
| Balanced auger | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std |
| Reversible carbon steel blade | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std |
| Hardox 400 blade | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| Stainless blade | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| Tivar blade | - | - | - | - | - | - | - | - | - | - | - | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| Lateral blades | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| Adjustable skid shoes carbone steel | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std |
| Hardox 400 skid shoes | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| Stainless skid shoes | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| Tivar skid shoes | - | - | - | - | - | - | - | - | - | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| Drive chain number | 60 | 60 | 60 | 60 | 60 | 60 | 60 | 60 | 60 | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 |
| Number of safety bolts | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 3 | 2 | 3 | 2 | 3 |
| Bearing - ductile iron casing | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std |
| P.T.O. shaft (Standard) | No 2 | No 2 | No 4 | No 4 | No 4 | No 4 | No 4 | No 4 | No 4 | No 6 | No 6 | No 6 | No 6 | No 6 | No 6 | No 6 | No 6 |
| 1000/540 reducer | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Cushion valve | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| Hitch category | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| Weight (lbs) approx. - 1 auger | 570 | 610 | 650 | 820 | 675 | 830 | 685 | 835 | 685 | 1100 | 1150 | 1185 | 1340 | 1225 | 1380 | 1265 | 1420 |

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE WEIGHT DOES NOT INCLUDE ACCESSORIES.



GENERAL SPECIFICATIONS

| MODELS | 1 AUGER ONLY (LP) | | 2 AUGERS | | 1 AUGER ONLY (LP) | | | 1 OU 2 AUGERS | | | 1 AUGER ONLY (LP) | | | 1 OU 2 AUGERS | | | PULL TYPE (1 AUGER) | | | |
|---------------------------------------|------------------------|------------|------------|------------|-------------------|------------|------------|---------------|-------------|-------------|-------------------|-------------|-------------|---------------|-------------|------------|---------------------|------------|-------------|--|
| | N86-280 | N86-280TR | N86-282 | N86-282TR | N92-280 | N92-280TR | N92-310 | N92-312 | N92-312TR | N98-280 | N98-310/N98-312 | N98-342 | N98-342TR | N104-342 | N104-342TR | N74-240INV | N92-260INV | N92-280INV | N102-310INV | |
| Recommended horse power | 60@85 | 60@85 | 60@85 | 60@85 | 75@120 | 75@120 | 85@120 | 85@120 | 85@120 | 85@120 | 85@120 | 100@150 | 100@150 | 100@150 | 100@150 | 25@40 | 50@75 | 60@85 | 85@120 | |
| Cutting width | 86" | 86" | 86" | 86" | 92" | 92" | 92" | 92" | 92" | 98" | 98" | 98" | 98" | 104" | 104" | 74" | 92" | 92" | 102" | |
| Cutting height | 37 1/2" | 37 1/2" | 42 1/2" | 42 1/2" | 37 1/2" | 37 1/2" | 38 1/4" | 42 1/2" | 42 1/2" | 37 1/2" | 37 1/2" / 42 1/2" | 47 1/2" | 47 1/2" | 47 1/2" | 47 1/2" | 30" | 32" | 32" | 37 3/4" | |
| Impeller RPM | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | |
| Impeller diameter | 28 1/2" | 28 1/2" | 28 1/2" | 28 1/2" | 28 1/2" | 28 1/2" | 31" | 31" | 31" | 28 1/2" | 31" | 34" | 34" | 34" | 34" | 24" | 26" | 28 1/2" | 31" | |
| Impeller depth | 12" | 12" | 12" | 12" | 12" | 12" | 13 1/2" | 13 1/2" | 13 1/2" | 13 1/2" | 13 1/2" | 13 1/2" | 13 1/2" | 13 1/2" | 13 1/2" | 9" | 11" | 12" | 13 1/2" | |
| Number of blades | 4 | 4 | 4 | 4 | 4 | 4 | 5 | 5 | 5 | 5 | 5 | 6 | 6 | 6 | 6 | 4 | 4 | 4 | 5 | |
| Impeller shaft diameter | 1 9/16" | 1 9/16" | 1 9/16" | 1 9/16" | 2" | 2" | 2" | 2" | 2" | 2" | 2" | 2" | 2" | 2" | 2" | 1 9/16" | 1 9/16" | 1 9/16" | 2" | |
| Balanced impeller | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | |
| Drum center height | 19" | 19" | 19" | 19" | 19" | 19" | 20 1/2" | 20 1/2" | 20 1/2" | 19" | 20 1/2" | 22" | 22" | 22" | 22" | 15 1/2" | 18 1/2" | 19" | 20 1/2" | |
| Removable rotary drum | - | Std | - | Std | - | Std | - | Std | - | Std | - | - | Std | - | Std | - | - | - | - | |
| Cylinder size | 2 1/2 X 8" | 2 1/2 X 8" | 2 1/2 X 8" | 2 1/2 X 8" | 2 1/2 X 8" | 2 1/2 X 8" | 2 1/2 X 8" | 2 1/2" X 8" | 2 1/2" X 8" | 2 1/2" X 8" | 2 1/2" X 8" | 2 1/2" X 8" | 2 1/2" X 8" | 2 1/2" X 8" | 2 1/2" X 8" | 2" X 4" | 2 1/2 X 8" | 2 1/2 X 8" | 2 1/2 X 8" | |
| Length closed | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | 14 1/4" | 20 1/4" | 20 1/4" | 20 1/4" | |
| Chute rotation | Manual | - | - | - | - | - | - | - | - | - | - | - | - | - | - | Opt. | - | - | - | |
| | Hydraulic cylinder | - | - | - | - | - | - | - | - | - | - | - | - | - | - | Opt. | - | - | - | |
| | Hydraulic motor (gear) | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Opt. | Std | Std | Std | |
| Manual deflector | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | |
| Hydraulic | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | |
| Semi-industrial chute (2nd deflector) | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Std | Std | Std | |
| Industrial chute | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | - | Opt. | Opt. | Opt. | |
| 24", 48" Industrial chute extension | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | - | Opt. | Opt. | Opt. | |
| Hydraulic telescopic chute | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | - | Opt. | Opt. | Opt. | |
| Main auger diameter | 23" | 23" | 23" | 23" | 23" | 23" | 23" | 23" | 23" | 23" | 23" | 23" | 23" | 23" | 23" | 17" | 17" | 20" | 22" | |
| Upper auger diameter (optional) | - | - | 13" | 13" | - | - | 13" | 13" | 13" | - | 13" | 17" | 17" | 17" | 17" | - | - | - | - | |
| Balanced auger | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | |
| Reversible carbon steel blade | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | |
| Hardox 400 blade | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | |
| Stainless blade | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | |
| Tivar blade | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | - | Opt. | Opt. | Opt. | |
| Lateral blades | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | |
| Adjustable skid shoes carbone steel | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | |
| Hardox 400 skid shoes | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | |
| Stainless skid shoes | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | |
| Tivar skid shoes | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | - | Opt. | Opt. | Opt. | |
| Drive chain number | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 100 | 100 | 100 | 100 | 60 | 80 | 80 | 80 | |
| Number of safety bolts | 2 | 2 | 2 | 2 | 3 | 3 | 3 | 3 | 3 | 2 | 2 | 3 | 3 | 3 | 3 | 2 | 2 | 2 | 2 | |
| Bearing - ductile iron casing | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | Std | |
| P.T.O. shaft (Standard) | No 6 | No 6 | No 6 | No 6 | No 8 | No 8 | No 8 | No 8 | No 8 | No 8 | No 8 | No 8 | No 8 | No 8 | No 8 | No 4 | No 6 | No 6 | No 8 | |
| 1000/540 reducer | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | - | - | - | - | |
| Cushion valve | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | |
| | Required | Required | Required | Required | Required | Required | Required | Required | Required | Required | Required | Required | Required | Required | Required | Opt. | Required | Required | Required | |
| Hitch category | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 1 | 2 | 2 | 2 | |
| Weight (lbs) approx. - 1 auger | 1400 | 1600 | 1430 | 1675 | 1630 | 1785 | 1795 | 1865 | 2065 | 1740 | 1965 | 2200 | 2400 | 2250 | 2450 | 685 | 1500 | 1850 | 2100 | |

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE WEIGHT DOES NOT INCLUDE ACCESSORIES.

NORMAND CO. LTD, 340 Taché, Saint-Pascal, Qc Canada G0L 3Y0

Phone: (418) 492-2712