

MODELS	GENERAL SPECIFICATIONS										
	E48-200 <i>Plus</i>	E54-220 <i>Plus</i>	E60-220 <i>Plus</i>	E66-220 <i>Plus</i>	E72-240 <i>Plus</i>	E78-250 <i>Plus</i>	E86-280 <i>Plus</i>	E94-280 <i>Plus</i>	E100-310 <i>Plus</i>	E108-310 <i>Plus</i>	E68-220INV
Recommended horsepower (HP PTO)	16 @ 40*	16 @ 40*	18 @ 40*	25 @ 40	25 @ 40	35 @ 70**	50 @ 80	50 @ 80	75 @ 125	75 @ 125	25 @ 40
Cutting width	48"	54"	60"	66"	72"	78"	86"	94"	100"	108"	68"
Cutting height	26"	28"	28"	28"	30"	31"	36"	36"	38 ½"	38 ½"	26 ¼"
Impeller RPM	540	540	540	540	540	540	540	540	540	540	540
Impeller diameter	20"	22"	22"	22"	24"	25"	28"	28"	31"	31"	22"
Impeller shaft diameter	1 ¼"	1 ¼"	1 ¼"	1 ¼"	1 ¼"	1 9/16"	1 9/16"	1 9/16"	2"	2"	1 ¼"
Impeller depth	7"	7"	8"	8"	8 ½"	9"	11"	11"	12"	12"	8"
Impeller center height	13 ½"	14 ½"	14 ½"	14 ½"	15 ½"	16"	18"	18"	20"	20"	14 ½"
Balanced impeller	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Number of blades	4	4	4	4	4	4	4	4	5	5	4
Main auger diameter	17"	17"	17"	17"	17"	17"	20"	20"	23"	23"	15"
Balanced auger	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Chute rotation on Polyéthylène	Manual	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
	Hydraulic motor (gear)	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Chute 1 or 2 deflectors (Option)	1 or 2	1 or 2	1 or 2	1 or 2	1 or 2	1 or 2	1 or 2	1 or 2	1 or 2	1 or 2	1
Manual deflector	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Hydraulic deflector	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Carbon steel blade	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std bolted
Adjustable skid shoes	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Storage foot	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	-
P.T.O shaft number	T20	T20	T20	T40	T40	T40	T60	T60	T80	T80	T40 long
Driving chain number	50	50	60	60	60	60	60	60	80	80	60
Number of safety bolts	2	2	2	2	2	2	2	2	3	3	2
Hitch category (QA = quick hitch)	1	1	1	1	1	1	2	2	2	2	1, QH
Approx. weight (lb)	501	532	590	616	652	738	1 089	1 117	1 670	1 707	698

➤ \* Use with a P.T.O. shaft T40 if more than 30 HP

\*\* Use with a P.T.O. shaft T60 if more than 40 HP

- The weight includes the regular chute, the rotation kit, the PTO shaft, the hydraulic cylinder for chute deflector and hardware.

*Specifications are subject to change without notice*