



HITCH YOUR TRACTOR TO HIGH PERFORMANCE

HYBRID SERIES	1 auger only			
	N74-250HYB	N82-260HYB	N92-280HYB	N100-310HYB
Recommended horsepower (HP PTO)	25 to 50	40 to 75	60 to 90	85 to 140
Cutting width	74"	82"	92"	100"
Cutting height	29"	30 3/4"	33"	35 3/4"
Impeller RPM	540	540	540	540
Impeller diameter	25"	26"	28 1/2"	31"
Impeller depth	9"	11"	12"	14 1/4"
Number of blades	4	4	4	5
Impeller shaft diameter	1 9/16"	1 9/16"	1 9/16"	2"
Balanced impeller	Std	Std	Std	Std
Drum center height	21 1/2"	22 1/2"	24 1/4"	26 1/2"
Chute rotation by hydraulic motor with valve (gear)	Std	Std	Std	Std
Semi industrial chute (2 deflectors)	Std	Std	Std	Std
Hydraulic deflector	Std.	Std.	Std	Std
Manual deflector	Opt.	Opt.	Opt.	Opt.
Cylinder for chute deflector	2" X 4"	2" X 6"	2 1/2" X 8"	2 1/2" X 8"
Main auger diameter	15"	16"	17"	18"
Balanced auger	Std	Std	Std	Std
Reversible carbon steel blade	Std	Std	Std	Std
Reversible Hardox 450 blade	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel blade	Opt.	Opt.	Opt.	Opt.
Tivar blade	Opt.	Opt.	Opt.	Opt.
Mobile lateral rubber skid shoes	Std	Std	Std	Std
Storage foot	Std	Std	Std	Std
Hoses holder	Std	Std	Std	Std
Driving chain number	60	80	80	100
Chain guard	Std	Std	Std	Std
Number of safety bolts	2	2	3	3
Key for driving shaft adjustment	Std	Std	Std	Std
Bearing ductile iron casing	Std	Std	Std	Std
PTO shaft standard	T40	T60	T60	T80
Hitch category (QH = Quick Hitch)	1, 1QH	1, 1QH, 2	2, 2QH	2, 2QH
Approx weight (lbs) - 1 auger	1 079	1 281	1 749	2 286

*The weight includes the chute, the cylinder for chute deflector, the rotation kit and the PTO shaft.*

*Specifications are subject to change without notice.*