



HITCH YOUR TRACTOR TO HIGH PERFORMANCE

	N54-240H	N60-240H	N68-250H	N74-250H
Recommended horsepower (HP PTO)	20 @ 40 *	20 @ 40 *	25 @ 45	25 @ 45
Cutting width	54"	60"	68"	74"
Cutting height	28 ½"	28 ½"	29 ½"	29 ½"
Impeller RPM	540	540	540	540
Impeller diameter	24"	24"	25"	25"
Impeller depth	7 ½"	7 ½"	9"	9"
Number of blades	4	4	4	4
Impeller shaft diameter	1 ¼"	1 ¼"	1 9/16"	1 9/16"
Balanced impeller	Std	Std	Std	Std
Drum center height	14"	14"	14 ½"	14 ½"
Cylinder for chute deflector	2" X 4"	2" X 4"	2" X 4"	2" X 4"
Chute rotation by hydraulic cylinder (Gear)	Std	Std	Std	Std
Hydraulic deflector	Std	Std	Std	Std
Manual deflector	Opt.	Opt.	Opt.	Opt.
Semi Industrial chute (2 deflectors)	Std	Std	Std	Std
Hoses holder	Std	Std	Std	Std
Main auger diameter	17"	17"	17"	17"
Balanced auger	Std	Std	Std	Std
Reversible carbon steel cutting edge	Std	Std	Std	Std
Reversible Hardox 450 cutting edge	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel cutting edge	Opt.	Opt.	Opt.	Opt.
Tivar cutting edge	Opt.	Opt.	Opt.	Opt.
Lateral blades	Opt.	Opt.	Opt.	Opt.
Adjustable carbon steel skid shoes	Std	Std	Std	Std
Adjustable Hardox 450 skid shoes	Opt.	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.
Driving chain	60	60	60	60
Storage foot	Std	Std	Std	Std
Number of safety bolts	2	2	2	2
Bearing ductile iron casing	Std	Std	Std	Std
PTO shaft - standard	T20	T20	T40	T40
Adjustable hitch	Std	Std	Std	Std
Hitch category (QH = quick hitch)	1, QH	1, QH	1, QH	1, QH
Approximative weight (lb) - 1 auger	717	751	854	872

\* Use with a PTO shaft T40 if more than 30HP  
 The weight includes chute, cylinder for chute deflector, rotation kit and PTO  
 Specifications subject to change without notice

