

GENERAL SPECIFICATIONS	32 RD3	34 RD3	36 RD3
Recommended horsepower (hp)	140 @ 300	160 @ 300	180 @ 300
Width - open (ft)	32'	34'	36'
Width - close (ft, in.)	10' 7"	10' 7"	10' 7"
Length - open (ft, in.)	40' 6"	40' 6"	40' 6"
Length - close (ft)	37'	38'	39'
Blade height (in.)	28.5"	28.5"	28.5"
Transport tire	16.5L x 16.1	16.5L x 16.1	16.5L x 16.1
3-wheel steerable tandem	Standard	Standard	Standard
Hitch (Class 3)	Standard	Standard	Standard
Industrial-type cutting edge	Standard	Standard	Standard
Triangle holder	Standard	Standard	Standard
Holder for hydraulic hoses	Standard	Standard	Standard
Reflecting strips	Standard	Standard	Standard
Proportional hydraulic circuit	Standard	Standard	Standard
RF control	Standard	Standard	Standard
Laser pole - GPS	Option	Option	Option
Antifriction Teflon (strongly recommended)	Option	Option	Option
Hardox 450 finishing teeth	Option	Option	Option
Teeth storage compartment	Option	Option	Option
Approximative weight (lbs)	14,000 lbs	14,250 lbs	14,500 lbs