



	E48-200Plus	E54-220Plus	E60-220Plus	E66-220Plus	E72-240Plus	E78-250Plus	E86-280Plus	E94-280Plus
Recommended horsepower (HP PTO)	16 to 40*	16 to 40*	18 to 40*	25 to 40	25 to 40	35 to 70**	50 to 80	50 to 80
Cutting width	48"	54"	60"	66"	72"	78"	86"	94"
Cutting height	26"	28"	28"	28"	30"	31"	36"	36"
Impeller RPM	540	540	540	540	540	540	540	540
Impeller diameter	20"	22"	22"	22"	24"	25"	28"	28"
Impeller shaft diameter	1 ¼"	1 ¼"	1 ¼"	1 ¼"	1 ¼"	1 9/16"	1 9/16"	1 9/16"
Impeller depth	7"	7"	8"	8"	8 ½"	9"	11"	11"
Impeller center height	13 ½"	14 ½"	14 ½"	14 ½"	15 ½"	16"	18"	18"
Balanced impeller	Std	Std	Std	Std	Std	Std	Std	Std
Number of blades	4	4	4	4	4	4	4	4
Main auger diameter	17"	17"	17"	17"	17"	17"	20"	20"
Upper auger diameter	-	-	-	-	-	-	-	-
Balanced auger	Std	Std	Std	Std	Std	Std	Std	Std
Chute rotation on Polyéthylène	Manual	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
	Hydraulic motor (gear)	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Chute 1 or 2 deflectors (Option)	1 or 2	1 or 2	1 or 2	1 or 2	1 or 2	1 or 2	1 or 2	1 or 2
Manual deflector	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Hydraulic deflector	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Carbon steel blade	Std	Std	Std	Std	Std	Std	Std	Std
Adjustable skid shoes	Std	Std	Std	Std	Std	Std	Std	Std
Storage foot	Std	Std	Std	Std	Std	Std	Std	Std
P.T.O shaft number	T20	T20	T20	T40	T40	T40	T60	T60
Driving chain number	50	50	60	60	60	60	60	60
Number of safety bolts	2	2	2	2	2	2	2	2
Hitch category (QA = quick hitch)	1	1	1	1	1	1	2	2
Approx. weight (lb)	468	499	557	583	619	705	1 077	1 105

➤ * Use with a P.T.O. shaft T40 if more than 30 HP ** Use with a P.T.O. shaft T60 if more than 40 HP
 The weight includes the regular chute, the rotation kit, the hydraulic cylinder for chute deflector and the PTO shaft.
 Specifications are subject to change without notice



	E100-310Plus	2 augers		2 augers			
		E100-312Plus	E108-310Plus	E108-312Plus	E68-240HYB	E74-240HYB	
Recommended horsepower (HP PTO)	75 to 125	75 to 125	75 to 125	75 to 125	25 @ 40	25 @ 40	
Cutting width	100"	100"	108"	108"	68"	74"	
Cutting height	38 ½"	38 ½"	38 ½"	38 ½"	28"	28"	
Impeller RPM	540	540	540	540	540	540	
Impeller diameter	31"	31"	31"	31"	24"	24"	
Impeller shaft diameter	2"	2"	2"	2"	1 ¼"	1 ¼"	
Impeller depth	12"	12"	12"	12"	8 ½"	8 ½"	
Impeller center height	20"	20"	20"	20"	20 ¼"	20 ¼"	
Balanced impeller	Std	Std	Std	Std	Std	Std	
Number of blades	5	5	5	5	4	4	
Main auger diameter	23"	23"	23"	23"	14"	14"	
Upper auger diameter	-	13"	-	13"	-	-	
Balanced auger	Std	Std	Std	Std	Std	Std	
Chute rotation on Polyéthylène	Manual	Opt.	Opt.	Opt.	Opt.	-	-
	Hydraulic motor (gear)	Opt.	Opt.	Opt.	Opt.	Std	Std
Chute 1 or 2 deflectors (Option)	1 or 2	1 or 2	1 or 2	1 or 2	2	2	
Manual deflector	Opt.	Opt.	Opt	Opt	Opt.	Opt.	
Hydraulic deflector	Opt.	Opt.	Opt	Opt	Std	Std	
Carbon steel blade	Std	Std	Std	Std	Std	Std	
Adjustable skid shoes	Std	Std	Std	Std	Std	Std	
Storage foot	Std	Std	Std	Std	Std	Std	
P.T.O shaft number	T80	T80	T80	T80	T40	T40	
Driving chain number	80	80	80	80	60	60	
Number of safety bolts	3	3	3	3	2	2	
Hitch category (QA = quick hitch)	2	2	2	2	1, QH	1, QH	
Approx. weight (lb)	1 656	1 866	1 693	1 908	696	715	

The weight includes the regular chute, the rotation kit, the hydraulic cylinder for chute deflector and the PTO shaft. Specifications are subject to change without notice