

Hydraulic snowblowers specifications



	N62-250HYD	N78-250HYD	N102-340HYD
Cutting width	62"	78"	102"
Cutting height	30"	30"	47 ½"
Impeller diameter	25"	25"	34"
Impeller depth	9"	9"	12"
Number of blades	4	4	6
Impeller shaft diameter	1 9/16"	1 9/16"	2"
Balanced impeller	Std	Std	Std
Chute rotation by hydraulic motor	Std	Std	Std
Hydraulic deflector	Std	Std	Std
Semi Industrial chute	Std	Std	Opt.
Hydraulic telescopic chute	Opt.	Opt.	Std
Auger diameter	16"	16"	23"
Balanced auger	Std	Std	Std
Reversible carbon steel cutting edge	Std	Std	Std
Reversible 450 steel cutting edge	Opt.	Opt.	Opt.
Reversible stainless steel cutting edge	Opt.	Opt.	Opt.
Tivar cutting edge	Opt.	Opt.	Opt.
Lateral cutting edge	-	-	Opt.
Adjustable carbon steel skid shoes	Std	Std	Std
Adjustable 450 steel skid shoes	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.
Ductile iron bearing casing	Std	Std	Std
Quantity of safety bolts	-	-	2
Drive chain	#80 HD	#80 HD	#100
Bath oil for drive chain	Std	Std	Std
Hydraulic distribution block controlling the rotation of the impeller and auger, chute rotation and action deflector	Std	Std	-
Hydraulic hoses	Std	Std	Std
Hitch Category	Skid steer Slip hitch	Skid steer Slip hitch	As per loader type
Rear hydraulic blade	Opt.	Opt.	-
14 Pins connector including wiring	Std	Std	-
Electro-hydraulic group with remote control for activation of auxiliary functions	-	-	Std
Approx. weight (lb)	1 300	1 450	3 950
Required loader characteristics			
High Flow Minimum	27 GPM to 3 000 PSI	27 GPM to 3 000 PSI	54 GPM to 3 500 PSI
Auxiliaries hydraulic (2) for rotation and deflector	Required	Required	-
Hydrostatic transmission	-	-	Required
24 volts electric system	-	-	Required