

ONE PIECE BOX

DUMP TRAILERS



HITCH YOUR TRACTOR TO HIGH PERFORMANCE

QUALITY, ROBUSTNESS, AND VERSATILITY



25816M

25 TONS OF CAPACITY



248M

2 TONS OF CAPACITY



458M

4 TONS OF CAPACITY



869M

8 TONS OF CAPACITY



12712M

12 TONS OF CAPACITY

248M | 458M | 869M | 12712M | 25816M

ONE PIECE BOX DUMP TRAILERS



	248M	458M	869M	12712M	25816M
CAPACITY	2 Tons	4 Tons	8 Tons	12 Tons	25 Tons
WEIGHT	875 lb	1 395 lb	2 580 lb	4 750 lb	10 000 lb
CAPACITY CUBE FT. / EXTENSION	42,5 Cube Ft.	62,5 Cube Ft.	98 / 129 Cube Ft.	152 / 277 Cube Ft.	386 / 496 Cube Ft.
STEEL EXTENSION, REMOVABLE	-	-	-	-	Option
HARDOX 450 DUMP BOX	-	-	-	-	Option
LOAD SURFACE	47 1/2" x 94"	59" x 100 1/2"	71 1/2" x 106"	86 1/2" x 141 1/2"	93 5/8" x 192 1/2"
FLOOR PLATE	12 ga.	11 ga.	1/4"	1/4"	1/4"
OVERALL WIDTH	52 1/2"	64 5/8"	77 1/2"	92 1/4"	105"
SIDE PANEL	10"	12"	16"	22"	37 1/2"
FRONT AND REAR PANEL	17" / 13 1/4"	17 7/8" / 17 1/4"	23"	40"	51 5/8" / 65 5/16"
HEIGHT PLATFORM TO GROUND	26"	34"	35 1/2"	47"	57 3/16"
OVERALL LENGTH	132 7/8"	154"	162"	212"	283"
TREAD	40 1/4"	50"	59"	72"	79 5/8"
SPINDLE	1 5/8"	1 3/4"	2 1/4"	3"	5"
SPINDLE IN OIL	-	-	-	-	Standard
AXLE	Tandem	Tandem	Tandem	Tandem	Tandem
HUB (BOLT QTY)	5	5	6	8	10
TANDEM PIVOT BOLT	1 1/4"	1 1/4"	1 3/4"	2"	2 3/4"
WHEEL AND TIRE	Wheels 6" x 10", Tires 20,5 x 8,0-10 6 Ply	Wheels 6" x 15", Tires 11L x 15 8 Ply	Wheels 8" x 15" Tires 11L x 15 8 Ply utility	Wheels W14C Tires 15,5 x 16,1" 10 Ply	Wheels 16" x 22,5" Tires 560/60R22,5
OVERALL HEIGHT	45"	58 7/8"	66 1/2"	87 1/2"	112"
WHEEL AND TIRE	-	Wheels 6" x 15" Tires 11L x 15 8 Ply HWY	-	Wheels 11,75" x 22,5" 425/65R22,5 (used mixer tires)	-
OVERALL HEIGHT	-	58"	-	89 1/2"	-
WHEEL AND TIRE	-	-	-	Wheels 16" x 22,5" 550/45R22,5 - 16 Ply (Flotation)	-
OVERALL HEIGHT	-	-	-	88 1/4"	-
OFF-CENTER BEAM SHAFT	Standard	Standard	Standard	Standard	Standard
AUTOMATIC OPENING AND CLOSING REAR PANEL	Standard	Standard	Standard	Standard	Standard
HORIZONTAL PANEL OPENING	-	-	-	-	Standard
CYLINDER SIZE	3" x 16" **	3 1/2 x 24"***	4" x 24"***	Tel. 3 sections	Tel. 3 sections
CYLINDER SIZE	1 double action	1 double action	1 double action	1 single action	1 single action
DUMPING ANGLE	47°	46,5°	49°	50°	50°
COUPLING HEIGHT	15 1/2"	19 1/2"	19 1/2"	21 1/2"	23 1/8"
FREE HEIGHT – LIFTED UP	8 1/2"	18 1/4"	15 1/4"	27"	33"
GRAIN DOOR	-	-	-	Standard	Standard
SWIVEL COUPLER (CLEVIS)	Standard	Standard	Standard	Standard	Standard
ELECTRIC BRAKES	-	Option	Option	-	-
HYDRAULIC BRAKES	-	-	-	Option	Standard
HYDRAULIC JACK	-	-	-	-	Standard
MECHANICAL JACK	Standard	Standard	Standard	Standard	-
ELECTRICAL PUMP (DUMP BOX)	Option	Option	Option	-	-
LIGHTS KIT	Option	Option	Option	Standard	Standard

** Cylinder under platform.

N.B. : Specification subject to change without notice, without obligation.



Normand Co. Ltd
cienormand.com



340 Tache Street
Saint-Pascal (QC) Canada G0L 3Y0
418 492-2712 • 1 888 666-7626
normand@cienormand.com