

	1 auger only (LP)						
	N54-240H	N60-240H	N68-250H	N74-250H	N74-270H	N82-270H N82-270HTR	N86-270H N86-270HTR
Recommended horsepower (HP PTO)	20 to 40*	20 to 40*	25 to 45	25 to 45	40 to 65	40 to 65	45 to 75
Cutting width	54"	60"	68"	74"	74"	82"	86"
Cutting height	28 ½"	28 ½"	29 ½"	29 ½"	34"	34"	34"
Impeller RPM	540	540	540	540	540	540	540
Impeller diameter	24"	24"	25"	25"	27 ½"	27 ½"	27 ½"
Impeller depth	7 ½"	7 ½"	9"	9"	11"	11"	11"
Number of blades	4	4	4	4	4	4	4
Impeller shaft diameter	1 ¼"	1 ¼"	1 9/16"	1 9/16"	1 9/16"	1 9/16"	1 9/16"
Balanced impeller	Std	Std	Std	Std	Std	Std	Std
Drum center height	14"	14"	14 ½"	14 ½"	18 ¾"	18 ¾"	15 ½"
Removable rotary drum	-	-	-	-	-	- / Std	- / Std
Cylinder for chute (deflector)	2" X 4"	2" X 4"	2" X 4"	2" X 4"	2" X 6"	2" X 6"	2" X 6"
Chute rotation by hydraulic motor (gear with)	Std	Std	Std	Std	Std	Std	Std
Hydraulic deflector	Std	Std	Std	Std	Std	Std	Std
Manual deflector	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Semi industrial chute (2 deflectors)	Std	Std	Std	Std	Std	Std	Std
Hydraulic telescopic chute	-	-	-	-	-	-	Opt.
Main auger diameter	17"	17"	17"	17"	19 ½"	19 ½"	19 ½"
Upper auger diameter	-	-	-	-	-	-	-
Balanced auger	Std	Std	Std	Std	Std	Std	Std
Reversible carbon steel blade	Std	Std	Std	Std	Std	Std	Std
Reversible Hardox 450 blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Tivar blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Lateral blades	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable carbon steel skid shoes	Std	Std	Std	Std	Std	Std	Std
Adjustable Hardox 450 skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Driving chain number	60	60	60	60	80	80	80
Hoses holder	Std	Std	Std	Std	Std	Std	Std
Storage foot	Std	Std	Std	Std	Std	Std	Std
Number of safety bolts	2	2	2	2	2	2	2
Bearing ductile iron casing	Std	Std	Std	Std	Std	Std	Std
Shaft P.T.O. standard	T20	T20	T40	T40	T60	T60	T60
1 000 to 540 reducer box	-	-	-	-	-	-	-
Adjustable hitch	Std	Std	Std	Std	Std	Std	Std
Hitch category (QH = quick hitch)	1, QH	1, QH	1, QH	1, QH	1, 1QH, 2	1, 1 QH, 2	1, 1 QH, 2
Approx. weight (lb) - 1 auger	717	751	854	872	1 109	1 175 1 278	1 296

* Use with a P.T.O. shaft T40 if more than 30 HP

➤ The weight includes the chute, the rotation kit, the hydraulic cylinder for chute deflector and the PTO shaft . Prices and Specifications are subject to change without notice