

NORMAND	1 auger only			
	N86-280H N86-280HTR	N92-280H	N92-300H N92-300HTR	N98-300H
Recommended horsepower (HP PTO)	60 to 85	60 to 85	75 to 100	75 to 100
Cutting width	86"	92"	92"	98"
Cutting height	36"	36"	38"	38"
Impeller RPM	540	540	540	540
Impeller diameter	28 ½"	28 ½"	30"	30"
Impeller depth	12"	12"	12"	12"
Number of blades	4	4	5	5
Impeller shaft diameter	1 9/16"	1 9/16"	1 ¾"	1 ¾"
Balanced impeller	Std	Std	Std	Std
Drum center height	17 ¾"	17 ¾"	21 ¼"	21 ¼"
Removable rotary drum	- / Std	-	- / Std	-
Cylinder for chute (deflector)	2 ½" X 8"	2 ½" X 8"	2 ½" X 8"	2 ½" X 8"
Chute rotation by hydraulic motor	Std	Std	Std	Std
Manual deflector	Opt.	Opt.	Opt.	Opt.
Hydraulic deflector	Std	Std	Std	Std
Semi industrial chute (2 deflectors)	Std	Std	Std	Std
Hydraulic telescopic chute	Opt.	Opt.	Opt.	Opt.
Hoses holder	Std	Std	Std	Std
Main auger diameter	23"	23"	23"	23"
Upper auger diameter	-	-	-	-
Balanced auger	Std	Std	Std	Std
Reversible carbon steel blade	Std	Std	Std	Std
Reversible Hardox 450 blade	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel blade	Opt.	Opt.	Opt.	Opt.
Tivar blade	Opt.	Opt.	Opt.	Opt.
Lateral blades	Opt.	Opt.	Opt.	Opt.
Adjustable carbon steel skid shoes	Std	Std	Std	Std
Adjustable Hardox 450 skid shoes	Opt.	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.
Storage foot	Std	Std	Std	Std
Driving chain number	80	80	80	80
Number of safety bolts	2	2	2	2
Bearing ductile iron casing	Std	Std	Std	Std
Shaft P.T.O. standard	T60	T60	T80	T80
1 000 to 540 reducer box	Opt.	Opt.	Opt.	Opt.
Adjustable hitch	Std	Std	Std	Std
Hitch category (QH = quick hitch)	2, QH	2, QH	2, QH	2, QH
Approx. weight (lb) - 1 auger	1 649 1 790	1 675	1 790 1 975	1 910

The weight includes the chute, the rotation kit, the hydraulic cylinder for chute deflector and the PTO shaft
Prices and Specifications are subject to change without notice