

	1 or 2 augers	1 auger only	1 or 2 augers	
	N98-342H N98-342HTR	N102-340H	N102-342H N102-342HTR	N112-342H N112-342HTR
Recommended horsepower (HP PTO)	100 to 160	100 to 160	100 to 160	100 to 160
Cutting width	98"	102"	102"	112"
Cutting height	48"	41 1/8"	48"	48"
Impeller RPM	540	540	540	540
Impeller diameter	34"	34"	34"	34"
Impeller depth	14 1/4"	14 1/4"	14 1/4"	14 1/4"
Number of blades	5	5	5	5
Impeller shaft diameter	2"	2"	2"	2"
Balanced impeller	Std	Std	Std	Std
Drum center height	21"	21"	21"	21"
Removable rotary drum	- / Std	-	- / Std	- / Std
Cylinder for chute (deflector)	2 1/2" X 8"	2 1/2" X 8"	2 1/2" X 8"	2 1/2" X 8"
Chute rotation by hydraulic motor	Std	Std	Std	Std
Manual deflector	Opt.	Opt.	Opt.	Opt.
Hydraulic deflector	Std	Std	Std	Std
Semi industrial chute (2 deflectors)	Std	Std	Std	Std
Hydraulic telescopic chute	Opt.	Opt.	Opt.	Opt.
Hoses holder	Std	Std	Std	Std
Main auger diameter	23"	23"	23"	23"
Upper auger diameter	17"	-	17"	17"
Balanced auger	Std	Std	Std	Std
Reversible carbon steel blade	Std	Std	Std	Std
Reversible Hardox 450 blade	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel blade	Opt.	Opt.	Opt.	Opt.
Tivar blade	Opt.	Opt.	Opt.	Opt.
Lateral blades	Opt.	Opt.	Opt.	Opt.
Adjustable carbon steel skid shoes	Std	Std	Std	Std
Adjustable Hardox 450 skid shoes	Opt.	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.
Storage foot	Std	Std	Std	Std
Driving chain number	100	100	100	100
Number of safety bolts	3	3	3	3
Bearing ductile iron casing	Std	Std	Std	Std
Shaft P.T.O. standard	T80	T80	T80	T80
1 000 @ 540 reducer box	Opt.	Opt.	Opt.	Opt.
Adjustable hitch	Std	Std	Std	Std
Hitch category (QH = quick hitch)	2, QH	2, QH	2, QH	2, QH
Approx. weight (lb) - 1 auger	2 537 2 772	2 316 -	2 560 2 774	2 664 2 878

- The weight includes the chute, the rotation kit, the hydraulic cylinder for chute deflector and the PTO shaft
Prices and Specifications are subject to change without notice