

HYBRID HYBRID EXTENSIBLE	1 AUGER ONLY				
	N60-240HYB	N74-250HYB	N82-260HYB N82-260HYB-EXT32	N92-280HYB N92-280HYB-EXT36	N100-310HYB N100-310HYB-EXT40
Recommended horsepower (HP PTO)	20 to 40	25 to 50	40 to 75	60 to 90	85 to 140
Cutting width	60"	74"	82"	92"	100"
Extensible panel	-	-	- / 32"	- / 36"	- / 40"
Cutting height	28"	29"	30 ¾"	33"	35 ¾"
Impeller RPM	540	540	540	540	540
Impeller diameter	24"	25"	26"	28 ½"	31"
Impeller depth	7 ½"	9"	11"	12"	14 ¼"
Number of blades	4	4	4	4	5
Impeller shaft diameter	1 ¼"	1 9/16"	1 9/16"	1 9/16"	2"
Balanced impeller	Std	Std	Std	Std	Std
Drum center height	20 ¼"	21 ½"	22 ½"	24 ¼"	26 ½"
Chute rotation by hydraulic motor	Std.	Std.	Std.	Std	Std
Hydraulic deflector	Std.	Std.	Std.	Std	Std
Manual deflector	Opt.	Opt.	Opt.	Opt.	Opt.
Cylinder for chute deflector	2" X 4"	2" X 4"	2" X 6"	2 ½" X 8"	2 ½" X 8"
Semi-industrial chute (2 deflectors)	Std	Std	Std	Std	Std
Auger diameter	14"	15"	16"	17"	18"
Balanced auger	Std	Std	Std	Std	Std
Reversible carbon steel cutting edge	Std	Std	Std	Std	Std
Reversible Hardox 450 steel cutting edge	Opt.	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel cutting edge	Opt.	Opt.	Opt.	Opt.	Opt.
Tivar cutting edge	Opt.	Opt.	Opt.	Opt.	Opt.
Mobile lateral rubber skid shoes	Std	Std	Std	Std	Std
Storage foot	Std	Std	Std	Std	Std
Hoses holder	Std	Std	Std	Std	Std
Driving chain number	60	60	80	80	100
Chain guard	Std	Std	Std	Std	Std
Number of safety bolts	2	2	2	3	3
Key for driving shaft adjustment	Std	Std	Std	Std	Std
Bearing ductile iron casing	Std	Std	Std	Std	Std
Shaft PTO std	T20	T40	T60	T60	T80
Hitch category (QH = Quick hitch)	1, 1 QH	1, 1 QH	1 & 2 QH	2 QH	2 QH
Approx weight (lb)	860	1 063	1 265 1 570	1 709 1 935	2 256 2450

The weight includes the chute, the cylinder for chute deflector, the rotation kit and the PTO shaft. Specifications are subject to change without notice